




Welcome
United States Patent and Trademark Office



» ABSTRACT P

[Help](#) [FAQ](#) [Terms](#) [IEEE Peer Review](#)
[Quick Links](#)

Welcome to IEEE Xplore®

- ☐ Home
- ☐ What Can I Access?
- ☒ Log-out

Tables of Contents

- ☐ Journals & Magazines
- ☐ Conference Proceedings
- ☐ Standards

Search

- ☐ By Author
- ☐ Basic
- ☐ Advanced
- ☐ CrossRef

Member Services

- ☐ Join IEEE
- ☐ Establish IEEE Web Account
- ☐ Access the IEEE Member Digital Library

Related Links

- ☐ Access the IEEE Enterprise File Cabinet

Print Format

[Search Results](#) [\[PDF FULL-TEXT 248 KB\]](#) [PREV](#) [NEXT](#) [DOWNLOAD CITATION](#)

Request Permissions
RIGHTS LINK

Formation and properties of ternary silicide ($\text{Co}_x\text{Ni}_{1-x}$)Si thin films

[Hong-Xiang Mo](#) [Xin-Ping Qu](#) [Jian-Hai Liu](#) [Guo-Ping Ru](#) [Bing-Zong Li](#)

Dept. of Electron. Eng., Fudan Univ., Shanghai, China;

This paper appears in: Solid-State and Integrated Circuit Technology, 1998. Proceedings. 1998 5th International Conference on

Meeting Date: 10/21/1998 - 10/23/1998

Publication Date: 21-23 Oct. 1998

Location: Beijing China

On page(s): 271 - 274

Reference Cited: 6

Number of Pages: xxi+973

Inspec Accession Number: 6319144

Abstract:

A ternary silicide ($\text{Co}_x\text{Ni}_{1-x}$)Si₂ formed by Ni and Co thin films or Ni, Co and Ti thin films deposited on a Si(100) substrate is studied. The results show that a highly conductive silicide ($\text{Co}_x\text{Ni}_{1-x}$)Si₂ can be formed by solid phase reaction of either Ni/Co/Si or Co/Ni/Si structures. The resistivity of the silicide films is in the range of (15-20) μΩ.cm. The formation temperature of ($\text{Co}_x\text{Ni}_{1-x}$)Si₂ is rather low compared the disilicides of Co and Ni. XRD data show that ($\text{Co}_x\text{Ni}_{1-x}$)Si₂ has a CaF₂ structure its lattice constant is between that of CoSi₂ and NiSi₂. ($\text{Co}_x\text{Ni}_{1-x}$)Si₂ can also be form by rapid thermal annealing of a Co/Ni/Ti/Si multilayer structure. A quite low x_{\min} val shown by RBS/channeling investigation. The joint has a better epitaxy quality as compared with that without a Ti interlayer. It is more uniform and has a good thermal stability and low resistivity. Experiments with two step annealing and chemical select etching demonstrate that a self-aligned silicided contact and a gate-level interconnection structure can be formed on Si wafers

Index Terms:

[Rutherford backscattering](#) [channelling](#) [cobalt compounds](#) [dielectric thin films](#) [electrical resistivity](#) [etching](#) [integrated circuit interconnections](#) [lattice constants](#) [nickel compounds](#) [thermal annealing](#) [thermal stability](#) [15 to 20 muohmcm](#) [CoNiSi₂-Si](#) [RBS](#) [Si](#) [Si\(100\) substr](#) [XRD](#) [channeling](#) [chemical selective etching](#) [formation temperature](#) [gate-level interconnectio](#) [structure](#) [lattice constant](#) [multilayer structure](#) [rapid thermal annealing](#) [resistivity](#) [self-aligned silicided contact](#) [solid phase reaction](#) [ternary silicide](#) [thermal stability](#) [thin films](#)

Documents that cite this document

There are no citing documents available in IEEE Xplore at this time.

[Search Results](#) [\[PDF FULL-TEXT 248 KB\]](#) [PREV](#) [NEXT](#) [DOWNLOAD CITATION](#)

[Home](#) | [Log-out](#) | [Journals](#) | [Conference Proceedings](#) | [Standards](#) | [Search by Author](#) | [Basic Search](#) | [Advanced Search](#) | [Join IEEE](#) | [Web Account](#) | [New this week](#) | [OPAC Linking Information](#) | [Your Feedback](#) | [Technical Support](#) | [Email Alerting](#) | [No Robots Please](#) | [Release Notes](#) | [IEEE Online Publications](#) | [Help](#) | [FAQ](#) | [Terms](#) | [Back to Top](#)

Copyright © 2004 IEEE — All rights reserved